



The fire extinguishers are ISO9001:2000  
Using high quality ABC dry powder.  
Pressure gases are nitrogen and helium.

#### Standard Equipment

- Multi-purpose application
- Suitable for class A B C fires
- Squeeze grip operation
- Complete with bracket
- Corrosion resistant finish
- ISO Standard
- Protective plastic base upon request
- Main composition: NH<sub>4</sub>H<sub>2</sub>P<sub>0</sub>4 75%+-2.625%

Valve	 SNG03-01
Pressure Gauge	 SNG04-09B
Hose Assembling	 SNG05-05
Bracket	 SNG06-07
Safety Pin	 SNG04-02
Seal	 SNG04-01

Model	PD2.5	PD5	PD10	PD20
Capacity (lb)	2.5	5	10	20
Out-Diameter (mm)	80	110	130	182
Volume (l)	1.25	2.5	5.65	11.3
Cylinder length (mm)	265	300	435	500
Cylinder weight (l)	0.56	1.18	2.1	12.1
Dry powder filled weight (kg)	1	2	4.5	9
Working pressure (bar)	12	12	12	13.5
Test pressure (bar)	25	25	25	27
Fire class	ABC	1A:10BC	1A:21BC	2A:55BC
			2A:55BC	27A144BC

