



The fire extinguishers are UL/ULC/USCG Listed.

Standard Equipment

- Suitable for class B and C fires
- Brass material valve with stainless steel handle
- Aluminum Cylinder
- 100% leakage detected
- Production under ISO9001
- Quality System

Valve		024314001
Seal		0714025
Lever		0202148
Rivet		0204029
Carry Handle		0203125
Valve Body		020504042
Bracket		070200007
Safety Gasket		022304009
Safety Disc		0233007
Safety Cap		0212043
O Ring		020601126
Valve Stem Assembly		0220110
Spring		020701010
Tube Holder		020601036
Dip Tube		080402020
Cylinder		050100089
Safety Pin		020901003
Chain		0210001
Connector		0242022
Hose Assembling		080100047
Hoop Assembly		070200015



Model	CO10Lb
Capacity (lb)	10
Cylinder diameter (mm)	175
Fire rating	10-B:C
Discharge time (s)	10
Extinguisher weight	26.7 lb (12.11kg)
Packing size LxWxH (mm)	295x185x510
Operation temperature (F)	-22 -120 (-30-49°C)
UL list number	EX 27916
Marine type	B.C. size I
USCG approval number	162.028 Ex26671

Transport classification: Non-flammable, Non toxic gas.
UN No. 1044 Class 2.2

