





























2.5 Gal wet chemical fire extinguisher.
The fire extinguishers are UL/ULC Listed.

Standard Equipment

- Suitable for class A K fires
- Brass plated valve with stainless steel handle
- Stainless steel cylinder
- 100% helium leak detected
- Production under ISO9001
- Quality System

Valve		024313026				
Seal		0714025				
Lever		0202118				
Rivet		0204029		0204057		
Carry Handle		0203089				
Valve Body		020504045				
Bracket		070200007		070200010		070100016
Screw		0715038				
Hanging Loop		0715037				
Hose Assembling		080100094				
Cylinder		050100092				
Safety Pin		020901003		020901033		
Chain		0210001				
Pressure Gauge		040332				
Valve Stem Assembly		0220021				
O Ring		020603009				
Spring		020701040				
Ring Nut		0234004				
Dip Tube Assembly		080408006				
Antioverfill Tube		2012029				
Strap		071118				
Hose Catch		071007				



Model	K
Capacity (lb)	9.46
Cylinder diameter (mm)	179.5
Fire rating	1-A:K
Discharge time (s)	10
Extinguisher weight	31.75 lb (14.40kg)
Packing size LxWxH (mm)	190x190x645
Operation temperature (F)	40 -120 (4.4-49°C)
UL list number	EX 28016
Marine type	/
USCG approval number	/

Transport classification: Non-flammable, Non toxic gas.
UN No. 1044 Class 2.2

